

KEY FOB

LF/HF RFID TRANSPONDERS



Key fob

Elatec's key fobs are available as EM4200 technology for low frequency and as MIFARE Classic technology for high frequency. They easily fit to a normal key ring and can be used in various industries and application areas.

TECHNICAL DATA

| | | |
|------------------------|--|--|
| HOUSING | ABS | |
| CHIP TYPES | EM4200, MIFARE Classic 1k | |
| DIMENSIONS (L X W X H) | 30 mm x 37 mm x 6.5 mm / 1.18 inch x 1.46 inch x 0.26 inch | |
| COLOUR | grey | |
| SRF | 125 ± 6 kHz at room temperature | 13.56MHz Reader Standard (ISO/IEC 15693, ISO/IEC 14443) |
| TEMPERATURE RANGE | Operating: -25°C up to +75°C / -13°F up to +167°F Storage: -25°C up to +75°C / -13°F up to +167°F | |
| WEIGHT | Approx. 4.5g | |
| ORDER CODE | MIFARE Classic EM4200 | ART10354 ART13530 |



Elevator



EV Chargers



Access



Shop POS



Fitness
Equipment



Ticket POS



PC Log-on



Document
Management



Driver ID



Vending



Parking



Gaming



Locker Locks



Time
Attendance



Industrial
PC

ELATEC GmbH • Zeppelinstr. 1 • 82178 Puchheim • Germany
P +49 89 552 9961 0 • F +49 89 552 9961 129 • E-Mail: info@elatec.com
elatec.com

ELATEC
RFID Systems

Elatec reserves the right to change any information or data in this document without prior notice. Elatec declines all responsibility for the use of this product with any other specification but the one mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. Disclaimer: All names used in this document are registered trademarks of their respective owners.